SPECIFICATION





LOA Hull length		14.04 m 13.55 m	46' 1" 44' 5"
LWL		12.20 m	40' 0"
Beam		4.38 m	14' 4"
Draft			
shallow keel		1.82 m	5' 12"
L-keel, medium		2.23 m	7' 4"
Displacement			
shallow keel	approx.	12.10 t	26,675 lbs
L-keel, medium		11.70 t	25,794 lbs
Engine Diesel			
standard	approx.	57.00 PS	57.00 hp
option	approx.	80.00 PS	80.00 hp
Fuel tank	approx.	210 I	55 gal
Fresh water	approx.	450 I	119 gal
CE Certifcate	A-10		
Design	judel / vrolijk & co		
Interior	HanseYachts Design		
Mast length above WL	approx.	20.60 m	67' 7"
Total sail area	approx.	103.00 m ²	1,109 sq ft
Main sail			
standard	approx.	60.00 m ²	646 sq ft
furling	approx.	48.00 m ²	517 sq ft

458

Model year 2019. Valid from 2019.01.01. All measurements/figures are approximate. Errors and omissions excepted. Specification and material can be changed without notice.

approx.

approx.

approx.

Self-tacking jib

Crossover

Gennaker



43.00 m²

93.00 m²

160.00 m²

463 sq ft


1,001 sq ft


1,722 sq ft



DECK LAYOUT & CABIN CONCEPT













HULL

- -6 hull windows (3 each side)
- GRP hull, isophthalic gelcoat, colour: Signal White (RAL 9003), 1st layer vinyl ester resin with balsa sandwich core.
- Waterline and cove line, isophthalic gelcoat, colour: Dark Grey (RAL 7043)

KEEL

- L-keel, cast iron, draft: 2.25 m
- GRP rudder with seawater resistant aluminium shaft and self-aligning bearings

LAYOUT & INTERIOR

- -A1: Master cabin with island double berth, storage space and a head with separate shower stall
- -B1: Saloon with L-galley and dining area on stb, lounge area with chart table and head with separate shower on port
- C2: 2 aft cabins with double berth and storage space
- -3-burner gas stove with oven, waste bin, 12 V fridge approx. 130 I, double stainless steel sink with mixing tab
- Interior furniture in high quality marine plywood, Satin Varnish
- Hanse companionway closing system
- Saloon table, folding
- Worktop in galley Black Quartz

WOOD (FURNITURE, FLOORBOARD)

- Furniture Mahogany Style, Satin Varnish
- Cupboards fronts in wood colour
- Floorboard Acacia

UPHOLSTERY, CARPETS & CURTAINS

- Mattrasses for all berths
- Upholstery Monte Carlo, colour: Cream

DECK & OUTSIDE EQUIPMENT

- GRP deck with antislip surface, isophthalic gelcoat, colour: Signal
 White (RAL 9003), 1st layer vinyl ester resin with balsa sandwich
 core. 1 cockpit locker on port and stb, stern locker port and stb,
 stowage for running rigging at helm position, anchor locker at bow.
- Teak on cockpit benches
- Teak on bathing platform

- Twin wheel steering system with emergency tiller
- -2 stainless steel steering wheels with leather cover
- Cockpit table, stainless steel with folding teak tops
- Pulpit and pushpit, stainless steel
- Railing, incl. stanchions and stainless steel wire
- Covered halyards and control lines lead to cockpit helm position, organizers and jammers, 6 retractable mooring cleats, handrail on coach roof, bow anchor fitting with step
- 2 LEWMAR 45 ST EVO manual halyard winches
- Bathing platform, manual fold-out with swimming ladder
- Life raft storage
- Anchor and forestay fitting
- Self tacking jib system
- Mainsheet system
- 7 large and 6 small deck hatches openable, anchor locker hatch, stowage on coach roof with acrylic glass hatch
- 4 deck coach roof windows acrylic glass next to companionway

RIG & SAILS

- Rig, anodized aluminium, deck stepped, with kicker, standing and running rigging and 2 reefs
- ELVSTRÖM Dacron sails full battened, main and jib

NAVIGATION & INSTRUMENTS

- Illuminated compass at each helm
- Navigation lights LED

PROPULSION

- Fuel tank, approx. 210 I
- Engine (Diesel, approx. 57 hp) saildrive, 3-blade fix propeller

EQUIPMENT

- 12 V and 230 V electric system with main panels and 230 V shore power and sockets
- AGM battery set, capacity: 1x 90 Ah + 1x 160 Ah AGM
- Country Version: EU / AUS
- Battery charger 50 A
- Manual toilet with sea water flush (B layout)
- Manual toilet with sea water flush (A layout)
- LPG gas system, stowage for 1 gas bottle







- Blackwater system (appr. 35 I) with deck extraction and seacock for head, electric and manual bilge pump
- Freshwater system with electric pump and 20 I hot water, heated by main engine
- Fresh water tank, appr. 450 I

ACCESSORIES

- Mast steps

SHIPPING & TRANSPORT

- CE Certificate cat. A 10
- Owners manual
- EC Type Examination Certificate

